


2.5G SFP PoE Switch

8GE(PoE)+2GE(Uplink)2SFP(2.5G)


- Total 120W Power Supply
- 8 ports PoE
- 2 ports Uplink
- 2 ports SFP (1G/2.5G)
- AI Watchdog Function
- 6KV Lightning & 8KV ESD Protection
- Support bt 60W High Power

Ports Description




- 1 1000Mbps PoE Ports
- 2 bt 60W Power Ports
- 3 1000Mbps Uplink Ports
- 4 1000/2500Mbps SFP Port

Dimension (mm)



Installation Diagram



Specifications

Model	8GE(PoE)+2GE(Uplink)2SFP(2.5G)
Ports	PoE (1~6):10/100/1000Mbps PoE ports (RJ45) PoE (7~8):10/100/1000Mbps PoE ports (RJ45),Support bt 60W High Power LAN(1~2):10/100/1000Mbps uplink ports (RJ45) SFP(1~2):1G/2.5G SFP ports
Transmission Rate	1G/2.5G: Full Duplex Only; 10/100Mbps: Full Duplex / Half Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:30Gbps
	Network Latency (1000Mbps): ≤16μs (use the 64byte package size)
	MAC address table: 8K
	Packet Forwarding Rate: 22.3Mpps
Networking Standard	IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3x Flow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input: AC 90~240V Total≤120W AI Watchdog: Port 1~8 Power Output: PoE1~6 Port:1/2(+52V),3/6(GND)≤30W PoE7~8 Port:1245(+52V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV ESD Protection:8KV
Physical Specifications	Size(L*W*H): 190mm*140mm*43mm, Weight: 1.03KG
Working Environment	Operating Temperature: -30°C~60°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% Non-condensing
	Storage Humidity: 5%~90% Non-condensing
Certification	CE
	FCC
	RoHS 2.0
Warranty	Whole Device: 1 year
Package Content	AC Power Cable,User Manual